

# Ge-T8-E3100 - Basic Small Craft Sensor Package



The Ge-T8-E3100 is the [Geshrinari Shipyards](#) system for the [Ge-T2-1C - "Kuma" Shuttle](#) their version of the [Ke-T8 "Kuma" Multi-role Shuttle](#), it became available in [YE 31](#).

The Ge-T8-E3100 provides the following.

## Short Range

### Multi-Band Radar

**Long range band** Used for navigation and avoiding obstacles.

- Max range: 100,000 km (60,000 miles)

**Short range band** This is for precision ground mapping, used for planetary navigation.

- Max range: 180 km (30 miles)

### Radar altimeter

Used to determine the altitude of the shuttle. It transmits a radar pulse from the bottom of the shuttle, and measures the time it takes for the pulse to return.

- Max elevation 9,146.34 meters (30,000 ft)

### Laser Range Finder

This is used by the *Kuma* during docking and landing maneuvers to provide precise measurements. The system is accurate to 2 cm, and provides rate of closure.

## Long Range

- Long-range gravimetric and magnetic resonance, distortion, and interferometry sensors and spectrometers
- Electromagnetic trans-space flux sensors and imaging scanners

## Subspace Mass Detector

- Range of 20 LY
- Faster than light

## Inertial Navigation

This is a basic 🌐 [inertial navigation system](#) which is used as a vital component of the navigation system and allows the shuttle to perform dead reckoning.

From:  
<https://wiki.stararmy.com/> - **STAR ARMY**

Permanent link:  
[https://wiki.stararmy.com/doku.php?id=corp:geshrinari\\_shipyards:component:ge-t8-e3100](https://wiki.stararmy.com/doku.php?id=corp:geshrinari_shipyards:component:ge-t8-e3100)

Last update: **2023/12/21 04:20**

